

STAINLESS STEEL SHEET

Type - Temper	Specification	Condition	Thickness	Sheet Size
301	MIL-S-5059 (AMS5519)	FULL HARD	0.025"	Per Square Ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.016"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.020"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.025"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.032"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.040"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.050"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.063"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.080"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.100"	10ft x 3ft
301	MIL-S-5059 (AMS5518)	½ Hard	0.125"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.012"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.016"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.020"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.025"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.032"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.040"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.050"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.063"	10ft x 3ft
301	MIL-S-5059 (AMS5517)	¼ Hard	0.080"	10ft x 3ft
321	AMS5510	Annealed	0.016"	10ft x 3ft
321	AMS5510	Annealed	0.020"	10ft x 3ft
321	AMS5510	Annealed	0.025"	10ft x 3ft
321	AMS5510	Annealed	0.032"	10ft x 3ft
321	AMS5510	Annealed	0.036"	Per Square Ft
321	AMS5510	Annealed	0.040"	10ft x 3ft
321	AMS5510	Annealed	0.050"	10ft x 3ft
321	AMS5510	Annealed	0.063"	10ft x 3ft
321	AMS5510	Annealed	0.080"	Per Square Ft
321	AMS5510	Annealed	0.080"	10ft x 3ft
347	AMS5512	Annealed	0.063"	Per Square Ft

201 STAINLESS STEEL SUPER-BUFFED WELDED ROUND TUBE

(Economical, replaces chrome, re-polishes after welding.)


OD Inches	WT Inches
0.750	0.065
0.875	0.065
1.000	0.065

STAINLESS STEEL TUBE



Type	Specification	Condition	OD Inches	WT Inches
T304	MIL-T-8504		0.250	0.020
T304	MIL-T-8504		0.250	0.028
T304	MIL-T-8504		0.250	0.035
T304	MIL-T-8504		0.375	0.035
T304	MIL-T-6845	1/8 Hard	0.250	0.028
T304	MIL-T-6845	1/8 Hard	0.250	0.035
T304	MIL-T-6845	1/8 Hard	0.313	0.020
T304	MIL-T-6845	1/8 Hard	0.3125	0.028
T304	MIL-T-6845	1/8 Hard	0.375	0.035
T304	MIL-T-6845	1/8 Hard	0.625	0.028
T304	MIL-T-6845	1/8 Hard	0.750	0.049
T304	MIL-T-6845	1/8 Hard	1.000	0.035
T304	MIL-T-6845	1/8 Hard	1.000	0.058
T316	ASTM-A-269		0.125	0.020
T316	ASTM-A-269		0.250	0.035
T321	MIL-T-8808		0.250	0.035
T321	MIL-T-8808		0.375	0.020
T321	MIL-T-8808		0.375	0.028
T321	MIL-T-8808		0.375	0.035
T321	MIL-T-8808		0.500	0.020
T321	MIL-T-8808		0.500	0.065
T321	MIL-T-8808		0.625	0.035
T321	MIL-T-8808		1.000	0.028
T321	MIL-T-8808		1.750	0.035
T321	MIL-T-8808		1.750	0.049
T321	MIL-T-8808		1.875	0.035
T321	MIL-T-8808		1.875	0.049
T321	MIL-T-8808		2.000	0.049

STAINLESS STEEL ROD



Type	Condition	Specification	Diameter Inches
17-4PH	Annealed	AMS5643	0.750
17-4PH	Annealed	AMS5643	1.125
17-4PH	Annealed	AMS5643	1.500
17-4PH	Annealed	AMS5643	2.000
321	Annealed	AMS5645	0.375
321	Annealed	AMS5645	0.750
321	Annealed	AMS5645	1.000
321	Annealed	AMS5645	1.500
321	Annealed	AMS5645	2.000
347	Annealed	AMS5646	0.250